Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (previously presented): A seat mounting structure for use in a vehicle, that lessens the risk of injury to an occupant in side-impact collisions, the seat mounting structure comprising:

a sensor system;

a linkage system that guides a seat vertically up and laterally toward a centerline of the vehicle in such a manner that the seat is uniformly displaced in a substantially curvilinear translation such that little or no tilting of the seat takes place; and

an inflation module comprising an inflator and an inflatable structure, wherein the inflatable structure inflates in response to the sensor system, wherein the inflation of the inflatable structure displaces the seat in accordance with the linkage system.

Claim 2 (original): The seat mounting structure of claim 1, wherein the inflation of the inflatable structure stiffens a floor structure of the vehicle to resist intrusion in a side-impact.

Claim 3 (original): The seat mounting structure of claim 2, wherein the inflatable structure comprises metal.

Claim 4 (original): The seat mounting structure of claim 3, wherein the thickness of the metal of the inflatable structure is in the range of about 0.04 inches to about 0.06 inches.

Claim 5 (original): The seat mounting structure of claim 2, wherein the inflatable structure comprises an elongated structure having two folded sidewalls.

Claim 6 (original): The seat mounting structure of claim 1, wherein the linkage system

comprises a bar, wherein the bar comprises a first end pivotally fixed in position with respect to

the vehicle and a second end pivotally fixed in position with respect to the seat, wherein the bar

pivots about the first end and the second end in response to inflation of the inflatable structure in

order to guide the seat vertically up and laterally toward the centerline of the vehicle.

Claim 7 (original): The seat mounting structure of claim 1, wherein the linkage system

comprises a track attached to a top portion of the inflation module, wherein the seat slides

laterally toward the centerline of the vehicle while the inflatable structure displaces the seat

vertically up.

Claim 8-9 (canceled)

Claim 10 (original): The seat mounting structure of claim 1, wherein the sensor system

comprises an anticipatory sensor system that initiates the inflation of the inflatable structure in

anticipation of an impending side impact.

Claim 11 (original): The seat mounting structure of claim 10, wherein the anticipatory

sensor system comprises an optical sensor.

Claim 12 (original): The seat mounting structure of claim 10, wherein the anticipatory

sensor system comprises a radar sensor.

Claim 13-14 (cancelled)

Claim 15 (currently amended): A seat mounting structure for use in a vehicle, that

lessens the risk of injury to an occupant in side impact collisions, the seat mounting structure

comprising:

a sensor system;

Page 3 of 9

a linkage system comprising a seat mount wherein the seat mount is structured such that upon actuation of the piston device the seat is moved in such a manner that little or no tilting of the seat takes place; and

an inflation module comprising a piston device, wherein the piston device actuates in response to the sensor system, wherein the seat mount is structured such that upon actuation of the piston device the seat is moved in such a manner that little or no tilting of the seat takes place, and wherein the seat is displaced vertically up and laterally toward a centerline of the vehicle.

Claim 16 (canceled)

Claim 17 (original): The seat mounting structure of claim 15, wherein the linkage system comprises a track attached to a top portion of the piston device, wherein the seat slides laterally toward the centerline of the vehicle while piston device actuates the seat vertically up.

Claim 18 (original): The seat mounting structure of claim 15, wherein the linkage system comprises a rail, wherein the rail guides the seat vertically up and laterally toward a centerline of the vehicle in response to a sensor system.

Claim 19 (original): The seat mounting structure of claim 15, wherein the displacement of the seat approximates curvilinear translation of the seat.

Claim 20 (original): The seat mounting structure of claim 15, wherein the seat mounting structure further comprises an anticipatory sensor system that actuates the piston device in anticipation of an impending side impact.

Claim 21 (original): The seat mounting structure of claim 20, wherein the anticipatory sensor system comprises an optical sensor.

Claim 22 (original): The seat mounting structure of claim 20, wherein the anticipatory sensor system comprises a radar system.

Claims 23-28 (canceled)

Claim 29 (previously presented): An inflation module for use in a vehicle, that stiffens a floor structure of a vehicle and which moves a seat of the vehicle to lessen the risk of injury to an occupant in side impact collisions, the inflation module comprising:

an inflator;

a linkage system that guides a seat vertically up and laterally toward a centerline of the vehicle in such a manner that the seat is uniformly displaced in a substantially curvilinear translation such that little or no tilting of the seat takes place; and

an elongated inflatable structure, securely attached to the floor structure, wherein the elongated inflatable structure is oriented perpendicular to a sidewall of the vehicle, wherein the inflatable structure comprises metal.

Claim 30 (original): The inflation module of claim 29, wherein a thickness of the metal of the inflatable structure is in the range of about 0.04 inches to about 0.06 inches.

Claim 31(original): The inflation module of claim 29, wherein the inflatable structure is disposed under a seat of the vehicle.

Claim 32 (previously presented): A method for lessening the risk of injury to an occupant in side-impact collisions using a the seat mounting structure comprising a linkage system, an inflation module, and a sensor system, the method comprising:

sensing an impending side impact;

actuating the inflation module to displace the seat mount; and

guiding the seat mount vertically up and laterally toward a centerline of the vehicle in such a manner that the seat travels in a generally curvilinear translation such that little or no tilting of the seat takes place.

Claim 33 (original): The method of claim 32, further comprising stiffening a floor structure of the vehicle to resist intrusion in a side-impact, via inflation of an inflatable structure.

Claim 34 (original): The method of claim 33, wherein the inflatable structure comprises a folded elongated metal inflatable structure.

Claim 35 (original): The method of claim 32, further comprising inflating a side airbag.

Claim 36 (new): The seat mounting structure of claim 15, wherein the floor is stiffened to further protect a vehicle occupant.